

??

REXSH0060-MO-MA-FO-SE	Motor (MO)	Material (MA)	Foot (FO)	Sealing (SE)	Model
• Motor choices (Pressure ratio)					MO=?
- Motor 1500 (23:1)	15				MO=15
- Motor 3000 (46:1)	30				MO=30
• Lower Material selection					MA=?
- Motor 1000 (11:1)		CS			MA=CS
- Stainless Steel		SS			MA=SS
• Foot selection					FO=?
- Follower plate (Ø=80mm)			FP		FO=FP
- Wall mounted (Inlet F 1" BSPP)			D1		FO=D1
- Bung Mounted 200 L.			D2		FO=D2
• Seal package selection					SE=?
- PTFE - Polytetrafluoroethylene (Teflon like properties)				01	SE=01
- PTFE + FEP (Encapsulated O-Ring: Teflon like properties over Viton or Silicone)				02	SE=02
- PE - Polyethylene (UHMWPE)				03	SE=03
- Leather				04	SE=04
- PTFEG (PTFE + Graphite impregnated)				05	SE=05
- PU (Polyurethane)				06	SE=06

??

Description	Part number
Flat Seal Follower Plate for 20-30L Drums - Ø 280-285 (pump foot Ø80)	151100100
Flat Seal Follower Plate for 30L Drums -Ø 305 (pump foot Ø80)	151100200
Flat Seal Follower Plate for 30L Drums -Ø 315 (pump foot Ø80)	151100300
Flat Seal Follower Plate for 40-60L Drums -Ø 350-360 (pump foot Ø80)	151100400
Flat Seal Follower Plate for 200L Drums -Ø 571 (pump foot Ø80)	151100500
Flat Double Seal Follower Plate for 200L Drums -Ø 571 (pump foot Ø80)	1055180301
Double O-Ring Follower Plate for 20L drum -Ø 280 (pump foot Ø80)	151101100
Double O-Ring Follower Plate for 30L drum -Ø 285 (pump foot Ø80)	151101200
Double O-Ring Follower Plate for 30L drum -Ø 305 (pump foot Ø80)	151101300
Double O-Ring Follower Plate for 30L drum -Ø 315 (pump foot Ø80)	151101400
Double O-Ring Follower Plate for 40-60L drum -Ø 360 (pump foot Ø80)	151101500
Double O-Ring Follower Plate for 200L drum -Ø 571 (pump foot Ø80)	151101600
Double O-Ring PTFE-Coated Follower Plate for 20L drum -Ø 280 (pump foot Ø80)	151102100
Double O-Ring PTFE-Coated Follower Plate for 30L drum -Ø 285 (pump foot Ø80)	151102200
Double O-Ring PTFE-Coated Follower Plate for 30L drum -Ø 305 (pump foot Ø80)	151102300
Double O-Ring PTFE-Coated Follower Plate for 30L drum -Ø 315 (pump foot Ø80)	151102400
Double O-Ring PTFE-Coated Follower Plate for 40-60L drum -Ø 360 (pump foot Ø80)	151102500
Double O-Ring PTFE-Coated Follower Plate for 200L drum -Ø 571 (pump foot Ø80)	151102600
Monocolumn elevator for 20 to 60 L. drums (not available in NA/China)	151080000
Monocolumn elevator for 200 L. drums (not available in NA/China)	151090000
Double column elevator for 20 to 60 L. drums (not available in NA/China)	151080500
Double column elevator for 200 L. drums (not available in NA/China)	151090500



13 chemin de Malacher - CS 70086
38243 MEYLAN Cedex - FRANCE
Phone: +33 (0)4 76 41 60 60 - Fax: +33 (0)4 76 41 60 90
www.sames.com

Sames reserves the right to modify its equipment or specifications without further notice. Documents, products and pictures shown are not contractual. Adresses en une marque déposée. - Réf. n° 1 222 301 - 202310 - (NA)

REXSON SH0060

Shovel Pump



REXSON ?? / ??

PUMPING BEYOND POSSIBLE.

- Robust and reliable
- Simple to maintain
- Configurable and versatile

Markets



BOND • PROTECT • BEAUTIFY





REXSON SH0060

Shovel Pump

This High Viscosity Shovel Pump is for high pressure applications. Used with Airless® and extrusion applications requiring low flow rates and small size footprint.



??



Triple Chrome Layer

The **REXSON pumps of the high viscosity range** have been designed with robustness in mind, and the aim of offering a high degree of modularity to follow your application. Unlike liquid fluid pumping, the high viscosity range imposes highly variable mechanical stresses from one product to another.

Double-acting shovel pumps are specifically designed to transfer fluid with a viscosity greater than **50,000 Cps** and operate from 25,000 Cps for products whose particular rheology makes them difficult to pump. These pumps **include a shovel** that facilitates feeding the pump inlet, allowing it to move high viscosity materials.

To create your own pump that will **meet your application specifications**, you will have to **select**:

- The **correct air motor** according to the maximum pressure,
- The **construction materials** according to the nature of the product,
- The **foot and mounting style** according to the product packaging, and your installation
- The **Seal pack** (see the Documents tab to get all necessary information on our website).

Our air motors are designed for maximum airflow with a pilot distributor to **allow fast inversion**. They are equipped with a large silencer to **avoid water freezing** at the motor outlet and can be controlled (start/stop) from a remote air control.

These pumps are used as feeding equipment directly from **open drums** installed on a elevator using a follower plate. Specific pumps can be used on **bung drums** applications.



?? ???

??	??	??
?? ? ? ? ?	360 (5.200)	bar (psi)
?? ? ? ? ?	6 (87)	bar (psi)
??	>50,000	cps
Pressure ratio (depending on air motor size)	31:1, 62:1	
?? ? ?	80 (176)	°C (°F)
?? ? ? ? ? ? ? ? ?	60	cc
15 ? ? ? ? ? ? ? ? ? ?	0.90 (0.23)	l/mn (gal/mn)
Free flowrate (@ 60 cycles/mn)	3.60 (0.95)	l/mn (gal/mn)
?? ? ?	1500, 3000	
?? ? ? ? ?	1/2" - 3/4" BSP (F)	
?? ? ? ? ?	3/4" BSP (F)	
Weight (fluid section only)	8 (17.6)	kg (lbs)
Weight range (air motor only)	5.5-7.2 (12.1-15.9)	kg (lbs)
Fluid inlet (Follower plate)	80mm	
Air consumption depending on motor size (see catalog)	---	
Stroke	120 (4.72)	mm (inch)

PERFORMANCE



??

M1 Power distributor: Wide passageway for maximum airflow

L1 Upper Body: The upper part of the pump is of robust construction and must be able to withstand the maximum pressures.

L2 Upper Valve: This valve allows material to pass from the lower chamber to the upper chamber of the pump. A conical valve is used to reduce pressure loss.

L3 Lower Valve: Uses a large conical valve to reduce the pressure loss through the pump and allow easy filling.

L4 Shovel: Feeds the product to pump inlet. Allows the pump to dispense high viscosity material.

PRODUCTIVITY

M2 The Cover: Very easy to remove and to access the repair parts

M3 The Pulse Output: The motor can be easily monitored thanks to an air pulse occurring at each reversal.

L5 Motor adaptation flange: Unique and robust assembly of the motor shaft connection to the pump shaft. Allows quick adaptation to different air motors to vary the pressure ratio of the pump.

L6 Guard: To guarantee the safety of the operators, this guard prevents contact with the moving shaft of the pump.

L7 Lower Body: The pump lower is adapted as needed to be fixed on a follower plate, immersed in a bung drum, or simply threaded for connection to a manifold.

SUSTAINABILITY

M4 Brass guiding ring: Enduring and accurate guidance system

M5 Camshaft inversion system: Very reliable reversal system

L8 Upper seals packing: Our pump range has a wide range of seal materials to suit all your needs.

L9 Rod and Cylinder: The piston shaft and the cylinder are made of triple chrome steel to ensure excellent abrasion resistance.

