

设备

Designation	Version	Fluid inlet	Suction rod	Drain rod	Paint filter	Air regulator	Seal	Part number
40F100 FLOWMAX WALL MOUNTED PUMP WITHOUT FILTER	Wall	M 26x125	25 mm (1")	♦	-	2	GT + GT	151786100
40F100 FLOWMAX WALL MOUNTED PUMP WITH FILTER	Wall	M 26x125	25 mm (1")	♦	♦	2	GT + GT	151786200
40F100 FLOWMAX TROLLEY MOUNTED PUMP W FILTER	Trolley	M 26x125	25 mm (1")	♦	♦	2	GT + GT	151786400

附件

Designation	Part number
DRAIN ROD D16 S/S CONNECTOR 18X125	049596000
TROLLEY 2 ARMS	051221000
BRACKET W. STRAPS	056100199
SUCTION ROD DIAM 25 (FITTINGS 26*125) FOR EOS PUMP	149596150
SCUTION ROD D25 (FITTINGS 26x125) FOR 200 L DRUM	149596160
GRAVITY HOPPER 6L FOR EOS PUMP	151140230
AIR REGULATOR KIT FOR AIRMIX SPRAYING	151740200
TROLLEY 1 ARM	151730140

组成部件

Designation	Part number
SEAL KIT FOR HYD F100	144960291
SERVICING KIT FOR HY. F100	144960292
POCHETTE JOINTS MOTEUR 2000/4	146270990
POCHETTE DE MAINTENANCE POUR MOTEUR 2000-4	146270996

# 40F100 无气Flowmax® 泵

Airless®无气喷涂 / 泵



- 采用Flowmax®技术，无需维护
- 可用于对湿气敏感和磨蚀性涂料
- 寿命更长

## 市场



萨麦丝客杜林喷涂设备（上海）有限公司 上海市松江区申港路3802号A9 电话: +86 21 5438 6060 传真: +86 21 5348 6090  
www.sames.com

SAMES 保留其修改设备参数 而不另行通知的权利。展示文件、产品图片不具有法律效力。© 2013-10




## 40F100 无气Flowmax® 泵

该泵可用于2把喷枪供料。


采用防泄漏技术，无需动态密封

sames kremlin

技术



Flowmax® 供料



GT 密封



双球泵技术



3层镀铬

### 性能:

大输出，可循环供应多把喷枪  
大吸力，可用于粘度高达4000 cps的涂料  
可提供涡轮气动马达，24/7全天候连续运行

### 生产力:

Flowmax®波纹管技术可确保完全密封（防尘） - 无需润滑杯  
是对湿气敏感的固化剂和UV涂料的理想之选

### 可持续性:

三铬不锈钢活塞和气缸，不锈钢球&碳钢底座，确保可长期使用  
流线型设计，零部件更少 - 反向系统可快速切换，确保恒定的涂料供应  
波纹管寿命10000000次循环 - 长达8年

描述

