

设备

描述	压力	喷嘴型号	喷嘴大小	配件	扳机	订购编号
Sflow 275	275 bar (4020 psi)	Flat	-	1/2 JIC	2 fingers	135740200
Sflow 275	275 bar (4020 psi)	Reversible	12-13 (515)	Swivel 1/2 JIC	2 fingers	135740225
Sflow 275	275 bar (4020 psi)	Flat	-	Swivel 1/4 NPSM	2 fingers	135740240
Sflow 275	275 bar (4020 psi)	Reversible	12-13 (515)	Swivel 1/4 NPSM	2 fingers	135740245
Sflow 275	275 bar (4020 psi)	Flat	-	1/2 JIC	4 fingers	135740400
Sflow 275	275 bar (4020 psi)	Reversible	14-13 (517)	Swivel 1/2 JIC	4 fingers	135740427
Sflow 275	275 bar (4020 psi)	Flat	-	Swivel 1/4 NPSM	4 fingers	135740440
Sflow 275	275 bar (4020 psi)	Reversible	14-13 (517)	Swivel 1/4 NPSM	4 fingers	135740447
Sflow 470	470 bar (6820 psi)	Flat	-	Swivel 1/2 JIC	4 fingers	135745420
Sflow 470	470 bar (6820 psi)	Reversible	18-13 (519)	Swivel 1/2 JIC	4 fingers	135745429
Sflow 470	470 bar (6820 psi)	Flat	-	Swivel 1/4 NPSM	4 fingers	135745440
Sflow 470	470 bar (6820 psi)	Reversible	18-13 (519)	Swivel 1/4 NPSM	4 fingers	135745449

附件

描述	材质	颜色	推荐喷嘴	订购编号
ADAPTOR FOR M11/16" SPRAYING HEAD				129740032
ADAPTOR FOR M7/8" SPRAYING HEAD				129740030
AIRLESS® FLAT TIP CALIBER XXXX				00000XXXX
AIRLESS® SKILL TIP CALIBER XXXX				00030XXXX
PACK OF 4 GUN FILTERS INOX BLUE 150 MESH / 100µ	Stainless steel	Blue	06-XX to 12-XX	129740082
PACK OF 4 GUN FILTERS INOX RED 200 MESH / 75µ	Stainless steel	Red	04-XX to 06-XX	129740081
PACK OF 4 GUN FILTERS INOX WHITE 50 MESH / 300µ	Stainless steel	White	18-XX to 100-XX	129740084
PACK OF 4 GUN FILTERS INOX YELLOW 100 MESH / 150µ	Stainless steel	Yellow	12-XX to 18-XX	129740083
PACK OF 4 GUN FILTERS PA BLUE 150 MESH / 100µ	PA	Blue	06-XX to 12-XX	129740182
PACK OF 4 GUN FILTERS PA RED 200 MESH / 75µ	PA	Red	04-XX to 06-XX	129740181
PACK OF 4 GUN FILTERS PA WHITE 50 MESH / 300µ	PA	White	18-XX to 100-XX	129740184
PACK OF 4 GUN FILTERS PA YELLOW 100 MESH / 150µ	PA	Yellow	12-XX to 18-XX	129740183
TIPTOP AIRLESS® REVERSIBLE TIP CALIBER XXXX				00040XXXX
NG22 SWIVEL FITTING 500BAR MF1/2JIC				129732425
SWIVEL FITTING NG22 500B M1/4NPS F1/2JIC				129732435

组成部件

描述	订购编号
Maintenance kit for Sflow 470 (needle and spring)	129740902
Maintenance kit for Sflow 275 (needle and spring)	129740901
4 finger trigger	129740007
2 finger trigger	129740006
Carbide seats, seals and diffusers (2 of each) for Sflow® and Xcite®+	129740908
Carbide seats, seals and diffusers (2 of each) for Sflow® and Xcite®+	129740909
Diffuser (package of 10)	129740910
Pack of 10 seals for deflector	129740911

Sflow™ 275 & 470

手动无气喷枪

Airless®无气喷涂 / 手动喷枪系列



坚固耐用，操作舒适

- 高传递效率81%
- 高雾化质量
- 专为重工业设计

市场



萨麦丝客杜林喷涂设备（上海）有限公司 上海市松江区申港路3802号A9 电话: +86 21 5438 6060 传真: +86 21 5348 6090 www.sames.com

涂胶 · 防腐 · 喷涂

SAMES 保留其修改设备参数之权利。展示文件 - 产品图片不具有法律效力。© 2013-10



# Sflow™ 275 & 470

## 手动无气喷枪

Sflow™ 手动无气喷枪可用作防腐性涂料喷涂，有275和470bar两种版本可选。这把喷枪可以有效节省涂料。其人机工程学设计在极端条件下提供了灵活性，是处理高固体含量涂料和高富锌底漆的理想选择。

SFlow™ 无气手动喷枪为工业应用有效节省涂料，传输效率为81%。它可靠而坚固的结构，加上舒适的握力和无疲劳的扳机，即使在最困难的情况下也能轻松完成喷涂。SFlow™ 无气手动喷枪优化效率，提升喷涂工人工作体验。多种喷嘴供选：扁平，可翻转或 Skill™。



### 技术参数

描述	值	单位
最大涂料压力	275 (4000) - 470 (6820)	bar (psi)
传递效率	81	%
最高涂料温度	60 (140)	°C (°F)
涂料出口	M 1/2 JIC / M 1/4 NPSM	
涂料旋转套件	M 1/2 JIC / M 1/4 NPSM	
扳机安全锁	◆	
抛光铝枪身	◆	
推荐涂料粘度范围	20s à 25000 cps	s CA4
噪音等级	88.6	dbA
不锈钢浸湿件	◆	
硬钢底座	◆	
旋转接头 (升级版本)	◆	
重量	597 (21)	g (oz)



### 技术




枪身Chevron 密封



反向喷嘴



无气喷涂技术



SKILL 无气喷嘴

## 性能

- 1 可靠的和可重复的喷涂质量: 高端碳化钨单独测试
- 3 嵌入式专利设计用于快速更换
- 8 多种类型喷嘴供您选择
- ◆ 安全加强-一只手指触发关闭枪,提示锁,安全保护

## 生产力

- 2 操作舒适，减轻疲劳
- 4 人体工学设计,舒适操控
- 5 内置勾枪设计
- 6 旋转手柄，更好的可操作性
- 7 智能快锁定位

## 可持续性

- 3 PA或不锈钢大面积过滤，防止堵塞
- 3 涂料通道从内到外，维护方便
- ◆ 专利触发保护：类似于扳手，一个过滤器提取器并帮助移除触发器



### 描述

